

Project:	
Type:	
Catalog #:	



STANDARD



OPTIONAL

ILLUMINATION

- Adjustable long lasting, efficient, ultra bright white LED lamp heads.
- One, 0.5W white LED per lamp head.
- Unique all-inclusive lamp, reflector and lens assembly.

ELECTRICAL

- Dual 120/277 voltage standard. Optional dual 120/230 voltage available.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- 3.6V long life, maintenance-free, rechargeable Ni-Cd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Universal knockout pattern on back plate for surface mount.
- Suitable for wall or ceiling mount.

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.


OPTIONS

- RC: Remote capacity of up to 1.0 watt.
- SPV: UL Listed for special voltage option.
- HL: Provides increased center-to-center spacing (2.0W per head).

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro rated for five years.
- UL Listed for damp locations (0°C – 30°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Certified to CEC under Title 20 Regulations.

DIMENSIONS



ORDERING INFORMATION

Sample Part Number: ECO-E-1

MODEL	HOUSING COLOR	OPTIONS
ECO-E-1	(blank) White	RC Remote Capacity ¹
	B Black	SPV 120/230 Volt 50/60Hz
		HL High Lumen LED ¹

NOTES:

¹ -HL and -RC options cannot be combined. 0.5W of remote capacity available standard with -HL option

Project:	
Type:	
Catalog #:	

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)			INPUT AMPS (A)		
	120V	230V	277V	120V	230V	277V
ECO-E-1	0.33	0.33	0.37	0.046	0.044	0.052
ECO-E-1 RC/HL	0.52	0.52	0.60	0.068	0.068	0.070

REMOTE LAMP COMPATIBILITY

MODEL NUMBER	BATTERY	REMOTE CAPACITY	COMPATIBLE REMOTE HEAD FAMILY													
			MRHLED	RHLED	RH16LED	RH16		RH		RHR		SRH		SRHLED		
				MV		6V	12V	6V	12V	6V	12V	6V	12V			
ECO-E-1-RC	3.6V	1W	X	X												
ECO-E-1-HL	3.6V	0.5W	X													