

<b>Project:</b>	
<b>Type:</b>	
<b>Catalog #:</b>	



### STANDARD



### OPTIONAL



## ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LEDs.

## ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

## MOUNTING

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

## HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- EZ snap-out Chevron directional indicators.
- Compact, low-profile design.


## OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.

## WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.

## DIMENSIONS



## ORDERING INFORMATION

Sample Part Number: ECOEZXTEU2RWEM

MODEL	No. of FACES	LETTER COLOR	HOUSING COLOR	BATTERY	OPTIONS
ECO-EZSXTEU	2 Universal Single/ Double Face	R Red	W White	(blank) AC-Only	SDT Self-Diagnostics <sup>1</sup>
		G Green	B Black	EM Battery Backup	2C-120 Dual Circuit with 120V input <sup>2</sup>
					2C-277 Dual Circuit with 277V input <sup>2</sup>

<sup>1</sup> Available only with EM units.

<sup>2</sup> Available only with AC units.

<b>Project:</b>	
<b>Type:</b>	
<b>Catalog #:</b>	

### ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
ECO-EZSXTEU-RED/GREEN/EM/2C/SDT	3.8	3.8	0.034	0.020